

■ SPECIFICATION 規格表

☆In specification, if there is a * mark in front of item, it is an optional specification.

☆規格表裏・前方有*記號者・為特別規格。

unit:mm

Specification / 規格	Model / 機型	SGS-2448 AH/AHD	SGS-2460 AH/AHD	SGS-2480 AH/AHD	SGS-24100 AH/AHD	SGS-24120 AH/AHD	SGS-24140 AH/AHD	SGS-24160 AH/AHD	SGS-24180 AH/AHD	SGS-3468 AHD	SGS-3488 AHD	SGS-34128 AHD
Working Surface of table. (W x L) 工作台面積 寬×長		600 x 1200	600 x 1500	600 x 2000	600 x 2500	600 x 3000	600 x 3500	600 x 4000	600 x 4500	850 x 1700	850 x 2200	850 x 3200
Max. Grinding surface. (W x L) 最大研磨面積 寬×長		600 x 1200	600 x 1500	600 x 2000	600 x 2500	600 x 3000	600 x 3500	600 x 4000	600 x 4500	850 x 1700	850 x 2200	850 x 3200
Max. Horizontal travel of table. 工作台左右最大行程		1350	1650	2150	2650	3150	3650	4150	4650	1850	2350	3350
Max. Cross travel of table. 工作台前後最大行程		620						870				
Distance between table surface and spindle center 工作台面與主軸中心最大距離		850						950				
Table speed 工作台左右速度		5 ~ 25 M/min(16 ~ 80 fpm)										
Automatic crossfeed of saddle (60HZ) 前後每次進刀量 60HZ		0 ~ 38 (0"~1.5")										
Vertical handwheel (1 gra) 上下手轉每一刻度		AH:0.002 (0.0001") / AHD:0.002 (0.0001")									0.002 (0.0001")/min scale	
Vertical handwheel (1 rev) 上下手輪每一轉		0.025 (0.0125")										
Crossfeed handwheel (1 gra) 前後手輪每一刻度		0.02 (0.001")										
Crossfeed handwheel (1 rev) 前後手輪每一轉		5 (0.2")										
Longitudinal travel adjustable (from-to) 左右行程調整距離		150 ~ 1300	150 ~ 1600	150 ~ 2100	150 ~ 2600	150 ~ 3100	150 ~ 3600	150 ~ 4100	150 ~ 4600	150 ~ 1800	150 ~ 2300	150 ~ 3300
Crossfeed travel adjustable (from-to) 前後行程調整距離		0 ~ 600 (0~23.6")									0 ~ 850	
Spindle motor 主軸馬達		10HP x 6			*15HP x 6P			15HP x 6P		15HP x 6P		
Hydraulic pump motor 油壓泵馬達		5HP x 6P	7½HP x 6P			10HP x 6P		15HP x 6P		10HP x 6P		15HP x 6P
Crossfeed motor 前後馬達		1/4HP x 6P										
Downfeed motor 上下馬達		AH:1HP x 4P/ AHD:DC SERVO									DC SERVO	
Grinding wheel (ODxTxID) 砂輪尺寸(外徑×厚度×內徑)		510 x 50 x 127 *510 x 75 x 203.2										
Spindle speed 60/50HZ 主軸速度 60/50HZ		1150 RPM/60HZ 960 RPM/50HZ										
Coolant motor 沖水馬達		1/4HP										
Max. Load capacity (addition to magnetic chuck) 工作台最大荷重		1200 kgs	1300 kgs	1500 kgs	1600 kgs	1800 kgs	2000 kgs	2200 kgs	2400 kgs	1800 kgs	2000 kgs	2400 kgs
Net Weight 機器重量		6500 kgs	7500 kgs	8500 kgs	9500 kgs	10500 kgs	11500 kgs	12500 kgs	13500 kgs	10000 kgs	11500 kgs	15500 kgs
Gross Weight 裝箱毛重		7700 kgs	8700 kgs	9900 kgs	10900 kgs	12100 kgs	13100 kgs	14300 kgs	15300 kgs	11500 kgs	13500 kgs	18000 kgs
Packing dimensions (L x W x H) 裝箱尺寸(長×寬×高)		4430 x 2800 x 2740	5570 x 2800 x 2740	7000 x 2800 x 2740	9200 x 2800 x 2740	10200 x 2800 x 2740	11200 x 2800 x 2740	12200 x 2800 x 2740	13200 x 2800 x 2740	6500 x 3300 x 3000	7600 x 3300 x 3000	10500 x 3300 x 3000

We follow a policy of continuous improvement of all our products, and reserve the right to change specifications, mechanics, or designs at any time without notice or obligation.

為使產品改良和創新・本公司保有權利・隨時變更規格・機構與設計・恕不另行通知或負任何責任。



林寶機械貿易私人有限公司

LIM POH MACHINERY TRADING PTE LTD

NO. 111, UBI AVE 4, CIVIC TERRACE WAREHOUSE, SINGAPORE 408761.

E-mail: enquiry@limpoh.com Website: http://www.limpoh.com

TEL: 6846 1138 FAX: 6841 2832

GST Reg. No. M2-0067812-5 Business Reg. No. 198404054E