

規格 SPECIFICATION

型號 MODEL			DY-560			DY-660			DY-760	
機型 ITEMS			1000G	1500G	2000G	2500G	3000G	3500G	4000G	5000G
中心 CENTERS	高度	Height	280mm(11")			330mm(13")			380mm(15")	
	兩心間距離	Admits between	1000 - 5000 mm							
旋徑 SWING	床面	Over bed	560mm(22")			660mm(26")			760mm(30")	
	橫送台面	Over cross slide	370mm(14 1/2")			470mm(18 1/2")			570mm(22 3/8")	
	凹口面	Over gap	900mm(35 3/8")			1000mm(39 3/8")			1100mm(43 3/8")	
主軸 SPINDLE	貫穿孔徑	Bored to pass	86mm(3-1/4") or 102mm(4")							
	鼻端	Nose	D1-8" camlock or A1-8"							
迴轉速 SPEEDS	級數	Number	12							
	範圍	Range(60Hz)	25-1250 r.p.m.							
馬達 MOTOR	三相	Three phase	7.5 Hp or 10 Hp(optional)							
床身 BED	長度	Length	2600	3100	3600	4100	4600	5100	5600	6600
	寬度	Width	410mm(16")							
	高度	Height	1330mm(52 3/8")							
導螺桿 LEADSCREW	直徑	Diameter	45mm(1 7/8")							
	螺紋	Thread	2 T.P.I. or 4 T.P.I. or 6 pitch							
車牙 THREADS	公制螺紋	Metric threads	P 0.8-14mm							
	英制螺紋	Inch threads	2-28 T.P.I.							
	模數螺紋	Module threads	0.5-7 MOD							
	徑節螺紋	D.P. threads	4-56 D.P.							
縱向進刀 LONGITUDINAL FEEDS	公制	Metric(36 Nos.)	0.05-0.70mm REV.							
橫向進刀 CROSS FEEDS	公制	Metric(36 Nos.)	1/2							
橫送台 CROSS SLIDE	寬度	Width	230mm(9")							
	行程	Travel	360mm(14")							
複式刀座 TOP SLIDE	寬度	Width	150mm(6")							
	行程	Travel	255mm(10")							
尾座 TAILSTOCK	心軸—外徑	Quill-Outer dia.	75mm(2 15/16")							
	—行程	-Travel	180mm(6 5/16")							
	—頂心斜度	-Morse taper	MT No.5							
重量 WEIGHT(APPROX.)	淨重—DY-560G	Net weight-DY-560G	2200, 2500, 2800, 3100, 3500, 3900, 4300, 5000 Kgs							
	DY-660G	DY-660G	2300, 2600, 2900, 3200, 3600, 4000, 4400, 5100 Kgs							
	DY-760G	DY-760G	2400, 2700, 3000, 3300, 3700, 4100, 4500, 5200 Kgs							

* 規範內容如有更改不另行通知。 Above specifications are subject to change without notice.

標準附件 STANDARD ACCESSORIES

凹口床身	1個	Gap bed	1PC
馬達	1個	Driving motor 7.5 Hp	1PC
中心頂針	2個	Centers M.T.5	2PCS
心軸套筒	1支	Center sleeve	1PC
工具箱及工具	1個	Tool box & kits	1PC
夾頭後盤	1個	Chuck back plate 10"	1PC
冷卻系統	1個	Coolant equipment	1PC
腳踩式剎車	1個	Foot operated brake	1PC
中心架	1個	Stationary steady	1PC
三點定位停止桿	1個	3-position stop bar	1PC
跟刀架	1個	Travelling steady(follow rest)	1PC

特別附件 SPECIAL ACCESSORIES

活動頂針	1組	Rolling center M.T.5	1PC
花盤	1個	Face plate 16" or 20"	1PC
三爪夾頭	1個	3-jaw universal chuck 10" or 12"	1PC
四爪夾頭	1個	4-jaw independent chuck 16", 18" or 20"	1PC
斜度附件	1個	Taper turning attachment	1PC
工作燈(鹵素)	1個	Work lamp(halogen type)	1PC
夾頭蓋	1個	Chuck guard	1PC
五位停止器	1個	5-position carriage stop	1PC
後方刀架	1個	Rear toolpost	1PC
縱向快速傳動	1個	Rapid longitudinal traverse	1PC
後擋泥板	1個	Rear splash guard	1PC



林寶機械貿易私人有限公司
LIM POH MACHINERY TRADING PTE LTD
 NO. 111, UBI AVE 4, CIVIC TERRACE WAREHOUSE SINGAPORE 408761.
 E-mail: enquiry@limpoh.com Website: http://www.limpoh.com
 TEL: 6846 1138 FAX: 6846 2832 H/P: 9788 0138