

油壓滾通式滾牙機系列



UM-75 規格 SPECIFICATION:

能率 Capacity	形式 Model	UM-75		
滾製螺絲外徑	Diameter range of threads rolled	ø10 ~ ø75		
節距範圍	Range of pitch rolled	1.0P ~ 10.0P		
滾製長度	Max.length of thread rolled	固定、滾通(長度無限) 兩用 in feed and thru feed both available		
滾輪轉數	Speeds of dies	20~50 r.p.m		
滾輪外徑	Max.diameter	ø198mm		
滾輪孔徑	Bore of cylindrical dies	ø70mm	keyway	14x7
滾輪厚度	Width of cylindrical dies	35, 70, 100, 150 mm		
滾輪軸行程間距	Max.Min.center distance of die-spindles	275~195mm		
滾製量	Output(pcs/min)	4~20		
滾輪軸傾角	Swivelling angle	±6°		
滾輪軸馬力	Machine motor	25 HP(18.75 kw)		
油壓馬力	Hydraulic motor	7 1/2 HP (5.5 kw)		
最高進給油壓力	Max.rolling pressure	60TONS		
重量(大約)	Net weight(Approx.)	4700kgs		
毛量(大約)	Gross weight(Approx.)	5200kgs		
機械佔地面積	Overall dimensions.(LxWxH)m/m	2600 mm x 2400 mm x 2400 mm		
裝箱尺寸	Hipping measurement.(LxWxH)m/m	2520 mm x 2240 mm x 2230 mm		